



Power Meter Monitor

Model: PMM0721

Document version: 1.1

Date: August 2021



Digital output 250VAC module

KEY FEATURES

- 2x Digital outputs 250VAC
- 5000V system/field isolation
- Highly compacted size
- DIN rail mounting
- IP54 protection degree
- Operating temperature: -20°C to +83°C

DESCRIPTION

PMM0721 is a two Opto-isolated channels 250VAC digital output module which transmits control signals from the CPU to the connected actuators. PMM0721 has the ability to deliver 2A to the connected load which makes it highly useful and applicable in a wide range of industrial practices and processes.

TECHNICAL DATA

Number of digital outputs	2
Signal type	Voltage
Voltage signal type	250VAC
Output characteristic	Potential-free
Output current per channel	2mA
Isolation	5000V system/field
Operating temperature	-20°C to +83°C
Degree of protection	IP54

MECHANICAL DATA

Width	66.5mm (2.6")
Height	113mm (4.5")
Depth	6mm (0.23")
Wight	50 g
Mounting type	Din rail

BLOCK DIAGRAM

NUMBER	SIDE	DESCRIPTION
1	CPU	GND
2	CPU	INPUT 1
3	CPU	VCC 3.3-5 VDC
4	FIELD	DIGITAL OUTPUT
5	FIELD	COMMON

